

**Heat Reflecting Silicone Rubber Sealed Fiberglass Fabric**  
**500°F / 260°C: Dual-Coat™ Aluminum Film One Side / Silicone Rubber One Side**  
**High Temperature & Radiant Heat Reflecting with Vapor Barrier**



- Heat reflecting side is aluminum film. Perfect for applications involving movement or flexing, such as for bellows construction.
- Protection from intense radiant heat up to 3000°F.
- Reflects more than 95% of the radiant heat that contacts its surface.
- Silicone Rubber side provides excellent vapor barrier and protection from lubricating oils, wash down, contamination, etc.

**Additional Technical Data**

Tensile Strength: Warp: 200 lbs/inch 35.72 kg/cm  
 Fill: 200 lbs/inch 35.72 kg/cm

Tear Strength: Warp: 20 lbs 9.07 kg  
 Fill: 20 lbs 9.07 kg

Burst Strength: 450 psi / 31.5 kg/cm<sup>2</sup>

Flame Resistance: Char length 1" max  
 Afterglow 20 seconds max  
 Flame Out 10 seconds max

<b>Dual-Coat™ Radiant Heat Reflective Protection Fabric</b>				
<b>Aluminum Film One Side / Silicone Rubber One Side</b>				
<b>Part Number</b>	<b>Weight oz/yd<sup>2</sup> / g/m<sup>2</sup></b>	<b>Thickness in / mm</b>	<b>Roll width in / mm</b>	<b>Price per Linear Yard</b>
F-FG-ALM-SR-1750-17	17 / 578	.017 / .432	50 / 1270	\$ 86.33

- Full rolls are 50 yards / 150 feet / 45.7 metres long
- This Product is Available By-The-Yard
- Discounts for full roll purchases
- Available as a tape - custom slitting to any width is available