

1000°F / 537°C: DeltaGlass™ Very High Temperature & Heat Resistant Fiberglass Cloth Fabric: *Premium Grade*



- Manufactured of texturized fiberglass yarns, has a 1000°F / 537°C continuous rating while providing high insulation value & excellent personnel protection.
- Good abrasion resistance and tensile strength.
- A high-performance very high temperature fabric, used in almost all industries for heat protection.
- Also Available with specialty coatings such as Vermiculite, PTFE (Teflon), Aluminum foil, Neoprene/Latex. Also available with wire insert.

1000°F / 537°C continuous rating, high insulation value & excellent personnel protection

DeltaGlass™ Very High Temperature & Heat Resistant Cloth Roll Fabric				
Part Number	Weight oz/yd²	Roll Width In / cm	Thickness In / mm	Price per Yard / Metre
Heat Treated Fiberglass Cloth Blanket				
F-FG-P-HT-3240-18	18	40 / 101	.032 / .81	\$ 20.16 / \$ 21.97
F-FG-P-HT-3260-18	18	60 / 152	.032 / .81	\$ 26.24 / \$ 28.60
Plain Fiberglass Cloth Blanket				
F-FG-P-6040-24	24	40 / 101	.060 / 1.52	\$ 26.85 / \$ 29.27
F-FG-P-6060-24	24	60 / 152	.060 / 1.52	\$ 37.23 / \$ 40.58
F-FG-P-6540-30	30	40 / 101	.065 / 1.65	\$ 30.18 / \$ 32.90
F-FG-P-6560-30 **	30	60 / 152	.065 / 1.65	\$ 42.36 / \$ 46.17
F-FG-P-7540-36	36	40 / 101	.075 / 1.91	\$ 32.64 / \$ 35.58
F-FG-P-7560-36	36	60 / 152	.075 / 1.91	\$ 60.60 / \$ 66.05
F-FG-P-9040-40	40	40 / 101	.090 / 2.29	\$ 35.16 / \$ 38.32
F-FG-P-9060-40	40	60 / 152	.090 / 2.29	\$ 62.52 / \$ 68.15
F-FG-P-12540-64	64	40 / 101	.125 / 3.18	\$ 71.32 / \$ 77.74
F-FG-P-12560-64 #	64	60 / 152	.125 / 3.18	\$ 117.60 / \$ 128.18
Coated Weld-Splatter Shield: Black Color with light Neoprene/Latex Binder to reduce fray				
F-FG-WS-3040-24	24	40 / 101	.030 / .79	\$ 22.53 / \$ 24.56
F-FG-WS-3060-24	24	60 / 152	.030 / .79	\$ 31.83 / \$ 34.69

Roll length is 150 Feet / 50 yards / 45 Metres. Please call for pricing on fabric with PSA

**** Note: This fabric has MSHA-BC-109 Approval. # Minimum quantities may apply for this fabric**

* Note: The PSA will burn off at temperatures above 400°F and should be used to facilitate installation. Material with PSA should not be used in confined areas at elevated temperatures without ventilation until all of the PSA has vaporized.

*** This fabric is a fiberglass / aramid blend, with stainless steel wire insert. Max continuous temperature is 650F

These Products are Available By-The-Yard / Metre: Discounts for full roll purchases