

## 950°F / 510°C to 5400°F / 2982°C: GraphTek Flexible Graphite Sheets and Rolls



- Plain or reinforced sheets, laminates and rolls.
- Available with 316 Stainless Steel Foil Insert, Tang Insert, 316 Stainless Steel Wire Insert, Mylar Insert
- Flexible Graphite is 99% Carbon, providing extreme heat protection, thermal dissipation, lubrication and electrical conductivity. Made from mineral (flake) graphite it is non metallic, but thermally and electrically conductive just like metals.
- Sheets are 39.4 inches x 39.4 inches and are cut from roll material.
- Premium grade has low sulphur content.

Service temperature range depends on surrounding conditions. Useable to 950°F / 510°C in an oxidizing atmosphere (standard air). Useable to 1500°F / 815°C in mild oxidizing or steam atmosphere and useable to 5400°F / 2982°C in non-oxidizing conditions.

GraphTek Flexible Homogeneous Graphite Sheet Roll					
Part Number	Thickness in inches	"A" 39.4" x 108' roll	"B" 39.4" x 39.4" Sheet	"C" 60" x 200' roll	"D" 5" x 108' roll
F-GRF-005-X	.005	\$ 182.50	\$ 56.25	NA	NA
F-GRF-010-X	.010	\$ 221.25	\$ 63.75	NA	NA
F-GRF-015-X	.015	\$ 260.00	\$ 73.75	\$ 635.00	NA
F-GRF-020-X	.020	\$ 338.75	\$ 85.00	\$ 1005.00	\$ 48.75
F-GRF-030-X	.030	\$ 492.50	\$ 107.50	NA	\$ 68.75
F-GRF-040-X	.040	\$ 595.00	\$ 131.25	NA	NA

GraphTek Flexible Homogeneous Graphite Sheet Roll Premium Grade					
F-GRF-P-015-X	.015		\$ 607.50	NA	NA
F-GRF-P-0625-X	.0625		\$ 1316.25	NA	NA

GraphTek Flexible Graphite Laminate Sheet: 39.4" x 39.4"					
F-GRF-316SS Foil		NA	\$ Call	NA	NA
F-GRF-316SS-Tang		NA	\$ Call	NA	NA
F-GRF-316SS-Wire		NA	\$ Call	NA	NA
F-GRF-Mylar		NA	\$ Call	NA	NA
F-GRF-CarbonSteel		NA	\$ Call	NA	NA

For the "X" value, Specify A, B, C or D in part number to correspond to the desired size