

**662°F / 350°C: FlameShield™ Nomex® Braided Sleeve  
 Premium Grade  
 High Temperature, Heat & Flame Resistant Expandable Sleeve**



- Soft and pliable.
- Halogen & asbestos free.
- 90,000 psi tensile strength.
- Cuts easily to length with scissors. Braid angle allows this sleeve to expand slightly to accommodate irregular surfaces and turns, splices and in-line connectors.
- Available in natural and green color.
- .016" wall thickness.

**662°F / 350°C continuous rating, high insulation value & excellent personnel protection**

<b>FlameShield™ High Temperature &amp; Heat Resistant Braided Nomex® Sleeve - Premium</b>			
<b>Part Number</b>	<b>Nominal ID</b>	<b>Size Range</b>	<b>Price per Spool 100ft / 25ft</b>
S-BN-M003-02-X-Y	1/8"	1/16" to 1/4"	\$ 44.66 / \$ 23.53
S-BN-M006-04-X-Y	1/4"	1/8" to 5/16"	\$ 180.25 / \$ 57.76
S-BN-M008-05-X-Y	5/16"	7/32" to 7/16"	\$ 209.75 / \$ 64.90
S-BN-M010-06-X-Y	3/8"	1/4" to 1/2"	\$ 240.00 / \$ 72.51
S-BN-M013-08-X-Y	1/2"	5/16" to 5/8"	\$ 326.06 / \$ 94.05
S-BN-M016-10-X-Y	5/8"	7/16" to 7/8"	\$ 415.33 / \$ 116.24
S-BN-M019-12-X-Y	3/4"	9/16" to 1"	\$ 512.06 / \$ 140.52
S-BN-M025-16-X-Y	1"	3/4" to 1 1/8"	\$ 865.75 / \$ 228.97
S-BN-M032-20-X-Y	1 1/4"	1" to 1 1/2"	\$ 1250.25 / \$ 325.43
S-BN-M038-24-X-Y	1 1/2"	1 1/4" to 1 3/4"	\$ 1442.75 / \$ 373.60
S-BN-M044-28-X-Y	1 3/4"	1 1/2" to 2"	\$ 1707.22 / \$ 439.67

**For the "X" value, use "100" for 100 foot spool, use "25" for 25 foot spool**

**For the "Y" value, use "NT" natural color, use "GN" for green color**

Please call for additional discount pricing when ordering multiple spools.

**This Product is NOT Available By-The-Foot – Spools Only**