


Kevlar® Braided Aramid Sleeve - Standard Wall

320°F / 160°C: Continuous Rating – Higher Temperature for Shorter Periods

FlameShield™ High Temperature, Heat Resistant High Strength & Cut Resistant Expandable Sleeve - Premium Grade – Standard Wall Thickness



- Kevlar sleeve is soft and pliable, highly flexible.
- Halogen & asbestos free.
- Fibers are 20 times stronger than steel for the same diameter. Highly cut resistant.
- Braid angle allows this sleeve to expand/contract slightly to accommodate irregular surfaces and turns, splices and in-line connectors. Expansion does cause surface coverage to reduce slightly.
- Available in natural (yellow) color.
- .045" / 1.14 mm wall thickness.
- This product is made from genuine Kevlar® aramid yarns. Kevlar® is a registered trademark of DuPont.

320°F / 160°C maximum continuous rating with high insulation value & excellent personnel protection. Short term exposure to 572°F / 300°C

FlameShield™ High Temperature & Heat Resistant Braided Kevlar® Aramid Sleeve - Premium

Part Number	Nominal ID	Size Range	Spool Length	Price per Spool	
			Bulk / Small		
S-K-SW-M006-04-X	1/4" / 6 mm	1/8" to 5/16"	500 / 50	\$ 291.25 / \$ 42.37	
S-K-SW-M013-08-X	1/2" / 13 mm	5/16" to 5/8"	250 / 50	\$ 373.76 / \$ 87.25	
S-K-SW-M019-12-X	3/4" / 19 mm	9/16" to 1"	250 / 50	\$ 561.24 / \$ 124.75	
S-K-SW-M025-16-X	1" / 25 mm	3/4" to 1 1/8"	200 / 25	\$ 599.21 / \$ 87.37	
S-K-SW-M032-20-X	1 1/4" / 32 mm	1" to 1 1/2"	125 / 25	\$ 467.54 / \$ 106.43	
S-K-SW-M038-24-X	1 1/2" / 38 mm	1 1/4" to 1 3/4"	100 / 25	\$ 516.75 / \$ 141.70	
S-K-SW-M044-28-X	1 3/4" / 44 mm	1 1/2" to 2"	100 / 25	\$ 650.00 / \$ 195.00	
S-K-SW-M051-32-X	2" / 51 mm	1 3/4" to 2 1/4"	100 / 25	\$ 801.37 / \$ 212.75	
S-K-SW-M064-40-X	2 1/2" / 64 mm	2 1/4" to 2 3/4"	100 / 25	\$ 847.50 / \$ 254.25	
S-K-SW-M076-48-X	3" / 76 mm	2 3/4" to 3 1/4"	100 / 25	\$ 1052.50 / \$ 315.75	
S-K-SW-M089-56-X	3 1/2" / 89 mm	3 1/4" to 3 3/4"	100 / 25	\$ 1477.50 / \$ 443.25	
S-K-SW-M102-64-X	4" / 102 mm	3 3/4" to 4 1/4"	100 / 25	\$ 1712.50 / \$ 513.75	

For the "X" value: "F" for By-The-Foot followed by length in feet (example: F66 = 66 feet) use "B" for Bulk Spool size, use "S" for Small Spool size

This Product is available only in full Spools

Kevlar® Braided Aramid Sleeve – Colored - Standard Wall

320°F / 160°C: Continuous Rating – Higher Temperature for Shorter Periods

FlameShield™ High Temperature, Heat Resistant High Strength & Cut Resistant Expandable Sleeve - Premium Grade – Standard Wall Thickness




Photo Unavailable

- Kevlar sleeve is soft and pliable, highly flexible.
- Halogen & asbestos free.
- Fibers are 20 times stronger than steel for the same diameter. Highly cut resistant.
- Braid angle allows this sleeve to expand/contract slightly to accommodate irregular surfaces and turns, splices and in-line connectors. Expansion does cause surface coverage to reduce slightly.
- Available in 6 colors.
- .045" / 1.14 mm wall thickness.
- This product is made from genuine Kevlar® aramid yarns. Kevlar® is a registered trademark of DuPont.

320°F / 160°C maximum continuous rating with high insulation value
& excellent personnel protection. Short term exposure to 572°F / 300°C

FlameShield™ High Temperature & Heat Resistant Braided Kevlar® Aramid Sleeve - Premium					
Part Number	Nominal ID	Size Range	Spool Length	Price per Spool	
			in feet		
			Bulk / Small		
S-K-SWC-M006-04-X-Y	1/4" / 6 mm	1/8" to 5/16"	500 / 50	\$ / \$ call	
S-K-SWC-M013-08-X-Y	1/2" / 13 mm	5/16" to 5/8"	250 / 50	\$ / \$ call	
S-K-SWC-M019-12-X-Y	3/4" / 19 mm	9/16" to 1"	250 / 50	\$ / \$ call	
S-K-SWC-M025-16-X-Y	1" / 25 mm	3/4" to 1 1/8"	200 / 25	\$ / \$ call	
S-K-SWC-M032-20-X-Y	1 1/4" / 32 mm	1" to 1 1/2"	125 / 25	\$ / \$ call	
S-K-SWC-M038-24-X-Y	1 1/2" / 38 mm	1 1/4" to 1 3/4"	100 / 25	\$ / \$ call	
S-K-SWC-M044-28-X-Y	1 3/4" / 44 mm	1 1/2" to 2"	100 / 25	\$ / \$ call	
S-K-SWC-M051-32-X-Y	2" / 51 mm	1 3/4" to 2 1/4"	100 / 25	\$ / \$ call	
S-K-SWC-M064-40-X-Y	2 1/2" / 64 mm	2 1/4" to 2 3/4"	100 / 25	\$ / \$ call	
S-K-SWC-M076-48-X-Y	3" / 76 mm	2 3/4" to 3 1/4"	100 / 25	\$ / \$ call	
S-K-SWC-M089-56-X-Y	3 1/2" / 89 mm	3 1/4" to 3 3/4"	100 / 25	\$ / \$ call	
S-K-SWC-M102-64-X-Y	4" / 102 mm	3 3/4" to 4 1/4"	100 / 25	\$ / \$ call	

For the "X" value: use "B" for Bulk Spool size, use "S" for Small Spool size


For the "Y" value use OR - Orange, BK - Black, BL - Blue, RD - Red and GR - Green, YL-Yellow

This Product is available only in Spool Lengths

Kevlar® Braided Aramid Sleeve - Thin Wall

320°F / 160°C: Continuous Rating – Higher Temperature for Shorter Periods

FlameShield™ High Temperature, Heat Resistant High Strength & Cut Resistant Expandable Sleeve - Premium Grade – Standard Wall Thickness



- Kevlar sleeve is soft, pliable, and highly flexible.
- Halogen & asbestos free.
- Fibers are 20 times stronger than steel for the same diameter..
- Highly cut resistant.
- Braid angle allows this sleeve to expand slightly to accommodate irregular surfaces and turns, splices and in-line connectors. Expansion does cause surface coverage to reduce.
- Available in natural (yellow) color.
- .02" / 0.508 mm wall thickness.

320°F / 160°C maximum continuous rating with high insulation value & excellent personnel protection. Short term exposure to 572°F / 300°C

FlameShield™ High Temperature & Heat Resistant Braided Kevlar® Aramid Sleeve - Premium

Part Number	Nominal ID	Size Range	Spool Length in feet Bulk / Small	Price per Spool Bulk Spool / Small Spool	Price per Foot
S-K-TW-M006-04-X	1/4" / 6 mm	1/8" to 5/16"	500 / 50	\$ 291.25 / \$ 42.37	\$ 1.68
S-K-TW-M013-08-X	1/2" / 13 mm	5/16" to 5/8"	250 / 50	\$ 373.76 / \$ 87.25	\$ 3.48
S-K-TW-M019-12-X	3/4" / 19 mm	9/16" to 1"	250 / 50	\$ 561.24 / \$ 124.75	\$ 4.98
S-K-TW-M025-16-X	1" / 25 mm	¾" to 1 1/8"	200 / 25	\$ 599.21 / \$ 87.37	\$ 6.98
S-K-TW-M032-20-X	1 1/4" / 32 mm	1" to 1 ½"	125 / 25	\$ 467.54 / \$ 106.43	\$ 8.51
S-K-TW-M038-24-X	1 1/2" / 38 mm	1 ¼" to 1 ¾"	100 / 25	\$ 516.75 / \$ 141.70	\$ 11.23
S-K-TW-M044-28-X	2" / 51 mm	1 ½" to 2"	100 / 25	\$ 801.37 / \$ 212.75	\$ 17.02

For the "X" value: "F" for By-The-Foot followed by length in feet (example: F66 = 66 feet) use "B" for Bulk Spool size, use "S" for Small Spool size

This Product is available By-The-Foot and in Spools

Kevlar® Aramid Fiber Shears / Cutters: See complete list at the end of Section 7

Kevlar® and aramid based products are difficult to cut due to their filament shear strength. Heavy duty scissors can sometimes cut these materials, but often fail quickly as the Kevlar quickly dulls the cutting edge.

Kevlar® Shears are specifically designed to cut Kevlar® and aramid products, and feature a serrated blade so that the fibers don't slip while cutting, holding the fiber in position and allowing for a greater shear force to be applied by the opposing blade.


These shears are Extra Heavy Duty, and can be used for other materials such as cutting steel wires and steel tie wraps.

Kevlar® is a registered trademark of the DuPont Corporation

Kevlar® Braided Aramid Sleeve - Heavy Wall

320°F / 160°C: Continuous Rating – Higher Temperature for Shorter Periods

FlameShield™ High Temperature, Heat Resistant, High Strength & Cut Resistant Expandable Sleeve - Premium Grade – Heavy Wall Thickness



- Soft and pliable, highly flexible.
- Halogen & asbestos free.
- 20 times stronger than steel.
- Highly cut resistant.
- Braid angle allows this sleeve to expand to accommodate irregular surfaces and turns, splices and in-line connectors.
- Available in natural (yellow) color.
- .056" / 1.42 mm wall thickness.

320°F / 160°C maximum continuous rating with high insulation value & excellent personnel protection. Short term exposure to 572°F / 300°C

FlameShield™ High Temperature & Heat Resistant Braided Kevlar® Aramid Sleeve – Premium Heavy Wall

Part Number	Nominal ID	Size Range	Spool Length In feet Bulk / Small	Price per Spool Bulk Spool / Small Spool	Price per Foot
S-K-HD-M006-04-X	1/4" / 6 mm	1/4" to 3/8"	500 / 50	\$ 1397.82 / \$ 152.50	\$ 6.10
S-K-HD-M013-08-X	1/2" / 13 mm	1/2" to 1"	250 / 50	\$ 1250.05 / \$ 262.50	\$ 10.50
S-K-HD-M025-16-X	1" / 25 mm	1" to 1 3/4"	200 / 25	\$ 1424.67 / \$ 190.63	\$ 15.48
S-K-HD-M032-20-X	1 1/4" / 32 mm	1 1/4" to 2"	125 / 25	\$ 1103.72 / \$ 232.50	\$ 18.60

For the "X" value: use "F" for By-The-Foot followed by length in feet (example: F66 = 66 feet)
use "B" for Bulk Spool size, use "S" for Small Spool size

This Product is available in By-The-Foot lengths and spools

Kevlar Aramid Fiber Shears / Cutters: See complete list at the end of Section 7

Kevlar products are difficult to cut due to their strength. Regular or heavy duty scissors can sometimes cut these materials, but often fail quickly as the Kevlar quickly dulls the cutting edge.

Kevlar Shears are specifically designed to cut Kevlar, and feature a serrated blade so that the fibers don't slip while cutting, holding the fiber in position and allowing for a greater shear force to be applied by the opposing blade.

These shears are Extra Heavy Duty, and can be used for other materials such as cutting steel wires and steel tie wraps.

Kevlar® is a registered trademark of the DuPont Corporation