1500°F / 815°C: Fiberglass Woven Tape with Vermiculite Coating: *Premium Grade*

Very High Temperature & Heat Resistant Plain & Bolt-Hole / LadderTape™



Vermiculite coated fibreglass tape is manufactured from texturized fiberglass yarns then coated with Vermiculite, a 100% inorganic dispersion.

Vermiculite coated tape will withstand temperatures up to 1500°F / 815°C constant exposure with excursions to 2000°F / 1093°F. Also offers additional abrasion resistance and stiffness.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTapeTM). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc. This is also called a Ladder-Tape or Bolt-hole tape.

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Available with and without Pressure Sensitive Adhesive (PSA).

1500°F / 815°C continuous rating, high insulation value & excellent personnel protection

| Very High Temperature & Heat Resistant Vermiculite Coated Fiberglass Tape Premium Grade Plain & Bolt-Hole / LadderTape™ | | | | | | | | | |
|----------------------------------------------------------------------------------------------------------------------------|------------------|-----|----------------------------------------|------------------------------------|------------------------------------|--|--|--|--|
| Part Number | Width in / mm | | Price per Roll By Thickness: A / B / C | | | | | | |
| | | | "A" thickness no PSA / with PSA | "B" thickness no PSA / with PSA | "C" thickness no PSA / with PSA | | | | |
| T-FG-VC-W-P-M013-08-X-Z** | .5 | 13 | \$ 79.50 / \$ 122.47 | \$ 93.33 / \$ 136.30 | NA | | | | |
| T-FG-VC-W-P-M019-12-X-Z** | .75 | 19 | \$ 81.20 / \$ 123.97 | \$ 96.67 / \$ 141.50 | \$ 153.30 / \$ 201.47 | | | | |
| T-FG-VC-W-P-M025-16-X-Z | 1.0 | 25 | \$ 82.93 / \$ 133.23 | \$ 99.83 / \$ 150.80 | \$ 206.50 / \$ 256.13 | | | | |
| T-FG-VC-W-P-M032-20-X-Z | 1.25 | 32 | \$ 85.57 / \$ 144.87 | \$ 111.27 / \$ 170.57 | \$ 231.57 / \$ 290.87 | | | | |
| T-FG-VC-W-P-M038-24-X-Z | 1.5 | 38 | \$ 87.50 / \$ 147.62 | \$ 114.58 / \$ 178.65 | \$ 268.83 / \$ 322.17 | | | | |
| T-FG-VC-W-P-M051-32-X-Z | 2.0 | 51 | \$ 93.67 / \$ 160.47 | \$ 128.90 / \$ 195.37 | \$ 288.07 / \$ 354.87 | | | | |
| T-FG-VC-W-P-M064-40-X-Z | 2.5 | 64 | \$ 100.67 / \$ 175.66 | \$ 144.31 / \$ 219.32 | \$ 323.03 / \$ 398.03 | | | | |
| T-FG-VC-W-P-M076-48-X-Z | 3.0 | 76 | \$ 111.93 / \$ 193.17 | \$ 167.03 / \$ 446.67 | \$ 366.33 / \$ 467.96 | | | | |
| T-FG-VC-W-P-M089-56-X-Z | 3.5 | 89 | \$ 123.03 / \$ 206.33 | \$ 182.11 / \$ 265.40 | \$ 398.78 / \$ 497.58 | | | | |
| T-FG-VC-W-P-M102-64-X-Z | 4.0 | 102 | \$ 135.40 / \$ 248.60 | \$ 198.20 / \$ 292.56 | \$ 443.17 / \$ 506.33 | | | | |
| T-FG-VC-W-P-M127-80-X-Z | 5.0 | 127 | \$ 157.57 / \$ 278.20 | \$ 262.73 / \$ 374.67 | \$ 535.66 / \$ 647.53 | | | | |
| T-FG-VC-W-P-M152-96-X-Z | 6.0 | 152 | \$ 162.97 / \$ 294.30 | \$ 286.43 / \$ 384.40 | \$ 590.50 / \$ 688.51 | | | | |

- For the "X" value, specify A, B or C in part number to correspond to the desired thickness A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm $C = \frac{1}{4}$ " / .250" / 6.35mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape. Same price either style.
- Add "-PSA" to the part number for tape with PSA coating.
- All tapes are 100 foot lengths.
- ** -08 / .5" / 13mm and -12 / .75" / 19mm width tapes are not available in Drop Warp

1500°F / 815°C: Fiberglass Woven Tape with Vermiculite Coating: Industrial Grade

Very High Temperature & Heat Resistant Plain & Bolt-Hole / LadderTape™



Vermiculite coated fiberglass tape is manufactured from texturized fiberglass yarns then coated with Vermiculite, a 100% inorganic dispersion.

Vermiculite coated tape will withstand temperatures up to 1500°F / 815°C constant exposure with excursions to 2000°F / 1093°F. Also offers abrasion resistant stability.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTapeTM). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc. This is also called a Ladder or Bolthole tape.

Industrial grade tape has a lower bulk than Premium grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Available with and without Pressure Sensitive Adhesive (PSA).

1500°F / 815°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant Vermiculite Coated Fiberglass Tape Industrial Grade Plain & Bolt-Hole / LadderTape™

| | Width in / mm | | Price per Roll By Thickness: A / B | | |
|-------------------------|------------------|-----|------------------------------------|------------------------------------|--|
| Part Number | | | "A" thickness no PSA / with PSA | "B" thickness no PSA / with PSA | |
| T-FG-VC-W-I-M013-08-X-Z | .5 | 13 | \$ 366.57* / \$ 482.90 *NOTE | \$ 85.56 / \$ 128.53 | |
| T-FG-VC-W-I-M019-12-X-Z | .75 | 19 | \$ 62.53 / \$ 110.70 | \$ 164.93 / \$ 244.61 | |
| T-FG-VC-W-I-M025-16-X-Z | 1.0 | 25 | \$ 66.84 / \$ 117.13 | \$ 87.37 / \$ 139.00 | |
| T-FG-VC-W-I-M032-20-X-Z | 1.25 | 32 | \$ 73.60 / \$ 132.90 | \$ 94.67 / \$ 150.63 | |
| T-FG-VC-W-I-M038-24-X-Z | 1.5 | 38 | \$ 75.06 / \$ 135.07 | \$ 96.90 / \$ 156.90 | |
| T-FG-VC-W-I-M051-32-X-Z | 2.0 | 51 | \$ 81.40 / \$ 148.20 | \$ 104.03 / \$ 170.83 | |
| T-FG-VC-W-I-M064-40-X-Z | 2.5 | 64 | \$ 101.43 / \$ 176.43 | \$ 124.90 / \$ 198.79 | |
| T-FG-VC-W-I-M076-48-X-Z | 3.0 | 76 | \$ 108.50 / \$ 190.07 | \$ 126.23 / \$ 207.81 | |
| T-FG-VC-W-I-M089-56-X-Z | 3.5 | 89 | \$ 114.96 / \$ 198.27 | \$ 136.23 / \$ 219.53 | |
| T-FG-VC-W-I-M102-64-X-Z | 4.0 | 102 | \$ 122.71 / \$ 215.87 | \$ 146.17 / \$ 239.33 | |
| T-FG-VC-W-I-M127-80-X-Z | 5.0 | 127 | \$ 145.13 / \$ 258.07 | \$ 164.80 / \$ 294.47 | |
| T-FG-VC-W-I-M152-96-X-Z | 6.0 | 152 | \$ 150.27 / \$ 281.80 | \$ 185.37 / \$ 316.70 | |

- For the "X" value, specify "A" or "B" in part number to correspond to the desired thickness. A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape Same price either style.
- Drop Warp not available in ½ and ¾ inch widths.
- * NOTE: 0.5" wide x 1/16" tape roll is 500 feet in length.

1500°F / 815°C: Fiberglass Woven Tape with Vermiculite Coating: *Premium Grade / Special Thin*Very High Temperature & Heat Resistant Plain & Bolt-Hole / LadderTape™



Vermiculite coated fibreglass tape is manufactured from texturized fiberglass yarns then coated with Vermiculite, a 100% inorganic dispersion.

Vermiculite coated tape will withstand temperatures up to 1500°F / 815°C constant exposure with excursions to 2000°F / 1093°F. Also offers additional abrasion resistance and stiffness.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTape TM). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc. This is also called a Ladder Tape or Bolt-hole tape.

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Available with and without Pressure Sensitive Adhesive (PSA).

1500°F / 815°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant Fiberglass Woven Plain & Bolt-Hole / LadderTape™ Premium Grade / Special Thin 1/32" / .0313" / 0.8mm Thickness

| | Width in / mm | | Price per Roll | |
|--------------------------|------------------|-----|----------------|-----------|
| Part Number | | | no PSA | with PSA |
| T-FG-VC-W-P-T-M013-08-X | .5 | 13 | \$ 26.43 | \$ 36.53 |
| T-FG-VC-W-P-T-M025-16-X | 1.0 | 25 | \$ 35.10 | \$ 49.30 |
| T-FG-VC-W-P-T-M038-24-X | 1.5 | 38 | \$ 48.73 | \$ 70.83 |
| T-FG-VC-W-P-T-M051-32-X | 2.0 | 51 | \$ 58.63 | \$ 85.43 |
| T-FG-VC-W-P-T-M064-40-X | 2.5 | 64 | \$ 70.13 | \$ 109.66 |
| T-FG-VC-W-P-T-M076-48-X | 3.0 | 76 | \$ 81.50 | \$ 133.83 |
| T-FG-VC-W-P-T-M089-56-X | 3.5 | 89 | \$ 93.90 | \$ 152.57 |
| T-FG-VC-W-P-T-M102-64-X | 4.0 | 102 | \$ 106.36 | \$ 171.33 |
| T-FG-VC-W-P-T-M114-72-X | 4.5 | 114 | \$ 117.40 | \$ 188.96 |
| T-FG-VC-W-P-T-M127-80-X | 5.0 | 127 | \$ 128.53 | \$ 206.60 |
| T-FG-VC-W-P-T-M140-88-X | 5.5 | 140 | \$ 139.56 | \$ 226.33 |
| T-FG-VC-W-P-T-M152 -96-X | 6.0 | 152 | \$ 150.57 | \$ 240.70 |

- This tape is 1/32" / .0313" / 0.8mm thick
- For the "X" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape.
- Add "-PSA" to the part number for tape with PSA coating.
- All tapes are 100 foot lengths.