1200°F / 648°C: DeltaGlass™ Woven Fiberglass Tape: Premium Grade Very High Temperature & Heat Resistant Plain & Bolt-Hole / Ladder Tape



Manufactured of texturized fiberglass yarns, this tape will withstand temperatures up to 1200°F / 648°C in continuous service. 100% asbestos free, this tape is a bright white color.

This tape offers superior insulating properties as well as low chloride content.

Offered in Plain and Drop Warp (also known as Bolt-Hole or LadderTape[™]). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc.

A Heat Treated version of this product is available - please enquire

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Also available with Pressure Sensitive Adhesive (PSA) (see following page in catalog).

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

| Part Number | Width in / mm | | Price per Roll By Thickness | | | | |
|------------------------|---------------|-----|--------------------------------------|--------------------------------------|--------------------------------------|--|--|
| | | | "A" thickness Price / Weight (lb) | "B" thickness Price / Weight (Ib) | "C" thickness Price / Weight (lb) | | |
| T-FG-W-P-M013-08-X-Z** | .5 | 13 | \$ 34.20 / 1.0 | \$ 44.43 / 2.2 | NA | | |
| T-FG-W-P-M019-12-X-Z** | .75 | 19 | \$ 49.60 / 1.6 | \$ 55.70 / 3.2 | \$ 88.87 / 6.9 | | |
| T-FG-W-P-M025-16-X-Z | 1.0 | 25 | \$ 36.73 / 2.1 | \$ 58.44 / 4.2 | \$ 128.26 / 9.8 | | |
| T-FG-W-P-M032-20-X-Z | 1.25 | 32 | \$ 38.73 / 2.5 | \$ 59.73 / 5.2 | \$ 146.83 / 12.6 | | |
| T-FG-W-P-M038-24-X-Z | 1.5 | 38 | \$ 40.13 / 3.0 | \$60.55 / 6.2 | \$ 174.43 / 14.6 | | |
| T-FG-W-P-M051-32-X-Z | 2.0 51 | | \$ 44.73 / 4.1 | \$ 70.80 / 8.2 | \$ 188.71 / 19.5 | | |
| T-FG-W-P-M064-40-X-Z | 2.5 | 64 | \$49.86 / 5.1 | \$ 82.20 / 10.2 | \$ 214.66 / 24.4 | | |
| T-FG-W-P-M076-48-X-Z | 3.0 | 76 | \$ 58.23 / 6.2 | \$ 99.20 / 12.2 | \$ 244.70 / 29.3 | | |
| T-FG-W-P-M089-56-X-Z | 3.5 | 89 | \$66.43 / 7.3 | \$ 110.86 / 14.2 | \$ 286.43 / 34.2 | | |
| T-FG-W-P-M102-64-X-Z | 4.0 | 102 | \$ 75.60 / 8.2 | \$ 123.16 / 16.5 | \$ 303.16 / 39.0 | | |
| T-FG-W-P-M114-72-X-Z | 4.5 | 114 | \$ 90.77 / 9.2 | \$ 163.21 / 18.5 | \$ 348.44 / 44.0 | | |
| T-FG-W-P-M127-80-X-Z | 5.0 | 127 | \$ 92.73 / 10.3 | \$ 169.93 / 20.5 | \$ 379.46 / 48.8 | | |
| T-FG-W-P-M140-88-X-Z | 5.5 | 140 | \$ 96.73 / 11.3 | \$ 177.93 / 22.5 | \$ 398.46 / 53.7 | | |
| T-FG-W-P-M152 -96-X-Z | 6.0 | 152 | \$ 117.03 / 12.3 | \$ 187.46 / 24.5 | \$ 423.10 / 58.6 | | |

Very High Temperature & Heat Resistant Fiberglass

For the "X" Value, specify A, B or C in part number to correspond to the desired thickness **A** = 1/16" / .0625" / 1.59mm **B** = 1/8" / .125" / 3.18mm $C = \frac{1}{4}$ " / .250" / 6.35mm

- For the "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape. Same price either version.
- All tapes are 100 foot / 30 metre lengths.
- Items with * may have higher minimum order quantities please call.
- ** -08 / .5" / 13mm and -12 / .75" / 19mm width tapes are not available in Drop Warp
- Heat Treated / Heat Cleaned Available: low smoke dimensionally set exceptionally clean

1200°F / 648°C: DeltaGlass™ Woven Fiberglass Tape: *Premium Grade* Very High Temperature & Heat Resistant Plain & Bolt-Hole / Ladder Tape with Adhesive PSA



Manufactured of texturized fiberglass yarns, this tape will withstand temperatures up to 1200°F / 648°C in continuous service. 100% asbestos free, this tape is a bright white color.

This tape offers superior insulating properties as well as low chloride content.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTapeTM). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc.

A Heat Treated version of this product is available – please enquire

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Also available without Pressure Sensitive Adhesive (PSA) (see previous page in catalog).

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant Fiberglass Woven Plain & Drop-Warp / Bolt-Hole / LadderTape™ - Premium Grade with PSA Adhesive

| B. (N. sha | Width in / mm | | Price per Roll By Thickness | | | | |
|----------------------------|------------------|-----|-----------------------------|------------------------|------------------------|--|--|
| Part Number | | | "A" thickness Price | "B" thickness Price | "C" thickness Price | | |
| T-FG-W-P-M013-08-X-Z-PSA** | .5 | 13 | \$ 77.17 | \$ 87.40 | NA | | |
| T-FG-W-P-M019-12-X-Z-PSA** | .75 | 19 | \$ 83.63 | \$ 92.60 | \$ 137.03 | | |
| T-FG-W-P-M025-16-X-Z-PSA | 1.0 | 25 | \$ 87.03 | \$ 100.23 | \$ 178.23 | | |
| T-FG-W-P-M032-20-X-Z-PSA | 1.25 | 32 | \$ 97.88 | \$ 117.03 | \$ 193.50 | | |
| T-FG-W-P-M038-24-X-Z-PSA | 1.5 | 38 | \$ 100.13 | \$ 119.87 | \$ 227.77 | | |
| T-FG-W-P-M051-32-X-Z-PSA | 2.0 | 51 | \$ 111.50 | \$ 137.27 | \$ 252.83 | | |
| T-FG-W-P-M064-40-X-Z-PSA | 2.5 | 64 | \$ 124.87 | \$ 157.20 | \$ 289.43 | | |
| T-FG-W-P-M076-48-X-Z-PSA | 3.0 | 76 | \$ 139.46 | \$ 180.70 | \$ 326.36 | | |
| T-FG-W-P-M089-56-X-Z-PSA | 3.5 | 89 | \$ 146.40 | \$ 193.86 | \$ 396.96 | | |
| T-FG-W-P-M102-64-X-Z-PSA | 4.0 | 102 | \$ 185.46 | \$ 216.00 | \$ 396.73 | | |
| T-FG-W-P-M114-72-X-Z-PSA | 4.5 | 114 | \$ 191.43 | \$ 247.63 | \$ 437.71 | | |
| T-FG-W-P-M127-80-X-Z-PSA | 5.0 | 127 | \$ 212.33 | \$ 281.20 | \$ 491.40 | | |
| T-FG-W-P-M140-88-X-Z-PSA | 5.5 | 140 | \$ 219.33 | \$ 288.20 | \$ 501.40 | | |
| T-FG-W-P-M152 -96-X-Z-PSA | 6.0 | 152 | \$ 227.36 | \$ 295.23 | \$ 518.20 | | |

- For the "X" Value, specify A, B or C in part number to correspond to the desired thickness A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm C = 1/4" / .250" / 6.35mm
- For the "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape. Same price either version.
- All tapes are 100 foot / 30 metre lengths.
- Items with * may have higher minimum order quantities please call.
- ** -08 / .5" / 13mm and -12 / .75" / 19mm width tapes are not available in Drop Warp
- Heat Treated / Heat Cleaned Available: low smoke dimensionally set exceptionally clean

1200°F / 648°C: DeltaGlass™ Woven Fiberglass Tape: *Premium Grade* Very High Temperature & Heat Resistant Plain Tape – EXTRA THICK



Manufactured of texturized fiberglass yarns, this tape will withstand temperatures up to 1200°F / 648°C in continuous service. 100% asbestos free, this tape is a bright white color.

This tape offers superior insulating properties as well as low chloride content.

This is the thickest woven fiberglass tape available at $9/32^{\circ} - 0.280^{\circ} - 7.2$ mm thick.

A Heat Treated version of this product is available – please enquire.

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

| Very High Temperature & Heat Resistant Fiberglass Woven Plain Tape – EXTRA THICK - Premium Grade | | | | | | |
|---|---------------|-----|------------------------------|--|--|--|
| Part Number | Width in / mm | | Price / Weight (lb) per roll | | | |
| T-FG-W-XTP-M025-16 | 1.0 | 25 | \$ 241.08 / 11.3 | | | |
| T-FG-W-XTP-M038-24 | 1.5 | 38 | \$ 320.67 / 16.8 | | | |
| T-FG-W-XTP-M051-32 | 2.0 | 51 | \$ 425.88 / 22.5 | | | |
| T-FG-W-XTP-M064-40 | 2.5 | 64 | \$ 498.86 / 28.1 | | | |
| T-FG-W-XTP-M076-48 | 3.0 | 76 | \$ 621.48 / 33.7 | | | |
| T-FG-W-XTP-M089-56 | 3.5 | 89 | \$ 678.53 / 39.4 | | | |
| T-FG-W-XTP-M102-64 | 4.0 | 102 | \$ 770.96 / 45.1 | | | |
| T-FG-W-XTP-M127-80 | 5.0 | 127 | \$ 1025.13 / 56.3 | | | |
| T-FG-W-XTP-M152-96 | 6.0 | 152 | \$ 1212.63 / 67.5 | | | |
| T-FG-W-XTP-M254-160 | 10.0 | 254 | \$ 1956.76 / 107 | | | |
| T-FG-W-XTP-M305-192 | 12.0 | 305 | \$ 2338.00 / 135 | | | |

- All tapes are 100 foot / 30 metre lengths.
- Available with CofC to MIL-I-24244C (Amend 1, IC 1, Type XVIII)
- Test Report is available at \$1565.00 per batch
- Minimum 6 rolls for 6", 10" and 12" widths, but check if we may have smaller minimum quantity available.

1200°F / 648°C: DeltaGlass™ Woven Fiberglass Tape: *Premium Grade* Very High Temperature & Heat Resistant Plain Tape: EXTRA WIDE



Manufactured of texturized fiberglass yarns, this tape will withstand temperatures up to 1100°F / 593°C in continuous service. 100% asbestos free, this tape is a bright white color.

This tape offers superior insulating properties as well as low chloride content.

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content).

A Heat Treated version of this product is available – please enquire

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant Fiberglass Woven Plain Tape: EXTRA WIDE - Premium Grade

| Devi Number | Width in / mm | | Price per Roll By Thickness | | | | |
|-----------------------|---------------|-----|--------------------------------------|--------------------------------------|--------------------------------------|--|--|
| Part Number | | | "A" thickness Price / Weight (lb) | "B" thickness Price / Weight (lb) | "C" thickness Price / Weight (lb) | | |
| T-FG-W-EWP-M178-112-X | 7 | 178 | \$ 257.60 / 14.4 | \$ 526.31 / 28.7 | \$ 1108.82 / 68.4 | | |
| T-FG-W-EWP-M203-128-X | 8 | 203 | \$ 296.47 / 16.4 | \$ 620.62 / 32.7 | \$ 1266.97 / 78.2 | | |
| T-FG-W-EWP-M228-144-X | 9 | 228 | \$315.54 / 18.5 | \$ 658.91 / 36.9 | \$ 1342.36 / 88.0 | | |
| T-FG-W-EWP-M254-160-X | 10 | 254 | \$ 352.45 / 20.6 | \$ 735.51 / 41.1 | \$ 1492.56 / 97.8 | | |
| T-FG-W-EWP-M279-176-X | 11 | 279 | \$ 389.25 / 22.7 | \$ 812.16 / 45.3 | \$ 1642.74 / 107.6 | | |
| T-FG-W-EWP-M305-192-X | 12 | 305 | \$ 429.05 / 24.8 | \$ 894.93 / 50.0 | \$ 1792.88 / 117.4 | | |

- Minimum order is 6 rolls
- For the "X" Value, specify A, B or C in part number to correspond to the desired thickness A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm C = 1/4" / .250" / 6.35mm
- All tapes are 100 foot / 30 metre lengths.

1200°F / 648°C: Fiberglass Woven Tape: *Industrial Grade* Very High Temperature & Heat Resistant Plain & Bolt-Hole / Ladder Tape



Manufactured of texturized fiberglass yarns, tape will withstand temperatures up to 1200°F / 648°C in continuous service.

This tape offers superior insulating properties as well as low chloride content.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTapeTM). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc. This is also called a Ladder or Bolthole tape.

A Heat Treated version of this product is available - please enquire

Industrial grade tape has a lower bulk than Premium grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fibreglass content). Available with and without Pressure Sensitive Adhesive (PSA).

| Very High Temperature & Heat Resistant Fiberglass Woven Plain & Bolt-Hole / Drop-Warp / LadderTape™ - Industrial Grade | | | | | | |
|---|-------|-----|------------------------------------|------------------------------------|--|--|
| | Width | | Price per Roll By Thickness: A / B | | | |
| Part Number | in / | | "A" thickness no PSA / with PSA | "B" thickness no PSA / with PSA | | |
| T-FG-WI-M013-08-X-Z** | .5 | 13 | \$ 102.63 / \$ 218.13 | \$ 37.30 / \$ 80.26 | | |
| T-FG-WI-M019-12-X-Z** | .75 | 19 | \$ 20.46 / \$ 69.40 | \$ 38.74 / \$ 86.22 | | |
| T-FG-W-I-M025-16-X-Z | 1.0 | 25 | \$ 23.90 / \$ 74.16 | \$ 38.56 / \$ 88.43 | | |
| T-FG-W-I-M032-20-X-Z | 1.25 | 32 | \$ 29.63 / \$ 88.53 | \$ 43.80 / \$ 99.20 | | |
| T-FG-W-I-M038-24-X-Z | 1.5 | 38 | \$ 29.86 / \$ 89.46 | \$ 45.48 / \$ 108.06 | | |
| T-FG-W-I-M051-32-X-Z | 2.0 | 51 | \$ 34.43 / \$ 101.76 | \$ 50.50 / \$ 117.83 | | |
| T-FG-W-I-M064-40-X-Z | 2.5 | 64 | \$ 48.63 / \$ 123.16 | \$ 65.80 / \$ 140.96 | | |
| T-FG-W-I-M076-48-X-Z | 3.0 | 76 | \$ 53.03 / \$ 135.23 | \$ 67.10 / \$ 147.50 | | |
| T-FG-W-I-M089-56-X-Z | 3.5 | 89 | \$ 59.66 / \$ 141.13 | \$ 78.66 / \$ 156.13 | | |
| T-FG-W-I-M102-64-X-Z | 4.0 | 102 | \$63.16 / \$157.93 | \$ 87.76 / \$ 168.53 | | |
| T-FG-W-I-M114-72-X-Z | 4.5 | 114 | \$ 71.46 / \$ 169.93 | \$ 94.51 / \$ 188.79 | | |
| T-FG-W-I-M127-80-X-Z | 5.0 | 127 | \$ 79.53 / \$ 191.70 | \$ 109.80 / \$ 203.96 | | |
| T-FG-W-I-M140-88-X-Z | 5.5 | 140 | \$ 92.17 / \$ 201.33 | \$ 120.27 / \$ 217.31 | | |
| T-FG-W-I-M152-96-X-Z | 6.0 | 152 | \$ 108.73 / \$ 213.00 | \$ 126.36 / \$ 229.63 | | |

- For the "X" value, specify "A" or "B" in part number to correspond to the desired thickness A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape Same price either version.
- All tapes are 100 foot / 30 metre lengths.
- Items with * may have higher minimum order quantities please call.
- ** .5"/13mm and .75"/19mm width tapes are not available in Drop Warp

1200°F / 648°C: Fiberglass Woven Tape: *Heat Treated – Heat Cleaned* Very High Temperature & Heat Resistant Plain Tape



Manufactured of texturized fiberglass yarns, tape will withstand temperatures up to 1200°F / 648°C in continuous service.

This tape offers superior insulating properties as well as low chloride content.

Heat Treated / Heat Cleaned tapes have very low smoke off when installed in high temperature applications, as the organics have been already mostly removed. Heat treating also sets the tape dimensionally.

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

| Very High Temperature & Heat Resistant Fiberglass Woven Plain Tape: Heat Treated / Heat Cleaned | | | | | | | |
|--|-----|-----|-----------|--|--|--|--|
| Part Number Width Price per Roll | | | | | | | |
| T-FG-W-HT-M025-16 | 1.0 | 25 | \$ 48.56 | | | | |
| T-FG-W-HT-M051-32 | 2.0 | 51 | \$ 62.50 | | | | |
| T-FG-W-HT-M064-40 | 2.5 | 64 | \$ 79.80 | | | | |
| T-FG-W-HT-M076-48 | 3.0 | 76 | \$ 81.10 | | | | |
| T-FG-W-HT-M102-64 | 4.0 | 102 | \$ 107.76 | | | | |

These are common ordered sizes: any of our tapes can be heat-treated/heat cleaned

- Tape thickness is .100"
- All tapes are 100 foot / 30 metre lengths.

1200°F / 648°C: Fiberglass Woven Tape: *Premium Grade / Special Thin* Very High Temperature & Heat Resistant Plain & Bolt-Hole / LadderTape™



Manufactured of texturized fiberglass yarns, this tape will withstand temperatures up to 1200°F / 648°C in continuous service.

This tape offers superior insulating properties as well as low chloride content.

Offered in *Plain* and *Drop Warp* (also known as Bolt-Hole or LadderTape[™]). Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for assembly onto access doors, etc.

A Heat Treated version of this product is available – please enquire

1200°F / 648°C continuous rating, high insulation value & excellent personnel protection

| Very High Temperature & Heat Resistant Fiberglass Woven Plain & Bolt-Hole / Drop-Warp / LadderTape™ Premium Grade / Special Thin 1/32" / .0313" / 0.8mm Thickness | | | | | | | |
|--|--------|-----|----------|-----------|--|--|--|
| Price per Roll | | | | | | | |
| Part Number | in / ı | nm | no PSA | with PSA | | | |
| T-FG-W-P-THIN-M013-08-X** | .5 | 13 | \$ 16.88 | \$ 27.43 | | | |
| T-FG-W-P-THIN-M025-16-X | 1.0 | 25 | \$ 24.20 | \$ 37.23 | | | |
| T-FG-W-P-THIN-M038-24-X | 1.5 | 38 | \$ 31.40 | \$ 54.13 | | | |
| T-FG-W-P-THIN-M051-32-X | 2.0 | 51 | \$ 37.73 | \$ 65.33 | | | |
| T-FG-W-P-THIN-M064-40-X | 2.5 | 64 | \$ 45.10 | \$ 85.90 | | | |
| T-FG-W-P-THIN-M076-48-X | 3.0 | 76 | \$ 52.53 | \$ 106.37 | | | |
| T-FG-W-P-THIN-M089-56-X | 3.5 | 89 | \$ 60.47 | \$ 120.86 | | | |
| T-FG-W-P-THIN-M102-64-X | 4.0 | 102 | \$ 67.80 | \$ 135.40 | | | |
| T-FG-W-P-THIN-M114-72-X | 4.5 | 114 | \$ 75.63 | \$ 149.30 | | | |
| T-FG-W-P-THIN-M127-80-X | 5.0 | 127 | \$ 82.73 | \$ 163.13 | | | |
| T-FG-W-P-THIN-M140-88-X | 5.5 | 140 | \$ 89.96 | \$ 176.47 | | | |
| T-FG-W-P-THIN-M152-96-X | 6.0 | 152 | \$ 96.90 | \$ 189.80 | | | |

- This tape is 1/32" / .0313" / 0.8mm thick
- For the "X" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape. Same price either style.
- Add "-PSA" to the part number for tape with PSA coating.
- All tapes are 100 foot / 30 metre lengths.
- ** -08 / .5" / 13mm width tapes are not available in Drop Warp