

**500°F / 260°C: 600 R Series MIL Spec Silicone Rubber Self Fusing
Compression & Stretch Electrical Insulating Tape**
Meets MIL-I-46852 / A-A-59163 & Many Other Proprietary Specifications
Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing within minutes, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets Mil-I-46852 and AA59163 specifications. Certification available.
- Standard roll length is 36 feet / 12 Yards / 10.9 Metres; other lengths available. For the XX value (color code): OR = Oxide-Red, BK = Black. For the "Z" Value: Substitute "CT" for Certified Tape or "NC" for Not Certified. Add \$6.00 for individual roll CofC. Lot/Batch CofC \$10.00 per order line item.

600 R Series MIL Spec High Temperature Silicone Self Fusing Compression/Stretch Electrical Insulating Tape Meets MIL-I-46852 and A-A-59163 Specifications				
Part Number	Tape Width Inches / mm	Thickness inches / mm	Type / Profile	Single Roll Price Per Roll
620 / 630 / 640 Mil-I-46852 / AA59163 Tapes: Type I				
T-SR-620-5-XX-Z	1/2 / 13	0.020 / 0.5	I / Rectangular	\$ 29.87
T-SR-620-75-XX-Z	3/4 / 19	0.020 / 0.5	I / Rectangular	\$ 32.76
T-SR-620-1-XX-Z	1 / 25	0.020 / 0.5	I / Rectangular	\$ 34.71
T-SR-620-1.5-XX-Z	1 ½ / 38	0.020 / 0.5	I / Rectangular	\$ 48.92
T-SR-620-2-XX-Z	2 / 51	0.020 / 0.5	I / Rectangular	\$ 50.88
T-SR-630-5-XX-Z	1/2 / 13	0.030 / 0.76	I / Rectangular	\$ 32.86
T-SR-630-75-XX-Z	3/4 / 19	0.030 / 0.76	I / Rectangular	\$ 36.04
T-SR-630-1-XX-Z	1 / 25	0.030 / 0.76	I / Rectangular	\$ 38.18
T-SR-630-1.5-XX-Z	1 ½ / 38	0.030 / 0.76	I / Rectangular	\$ 53.81
T-SR-630-2-XX-Z	2 / 51	0.030 / 0.76	I / Rectangular	\$ 55.97
T-SR-640-5-XX-Z	1/2 / 13	0.040 / 1.0	I / Rectangular	\$ 36.15
T-SR-640-75-XX-Z	3/4 / 19	0.040 / 1.0	I / Rectangular	\$ 39.64
T-SR-640-1-XX-Z	1 / 25	0.040 / 1.0	I / Rectangular	\$ 41.99
T-SR-640-1.5-XX-Z	1 ½ / 38	0.040 / 1.0	I / Rectangular	\$ 59.19
T-SR-640-2-XX-Z	2 / 51	0.040 / 1.0	I / Rectangular	\$ 61.57

Please enquire for pricing on sizes other than those listed above.
This tape can be made in thicknesses from 0.010" to 0.080" and in various widths.

Amalgamating time: At 120°C; 120 minutes / at 150°C; 35 minutes / at 200°C; 20 minutes / at 250°C; 15 minutes

Tested for short duration fluid resistance: Jet Fuel (JP5), Hydraulic Fluid (Skydrol 500B4), Mineral Oil (NATO 0142), Synthetic Oil (NATO 0156), MIL-C-87836 & Foran 141B cleaning fluids, MIL-A-8243 cooling fluid.