

500°F / 260°C: Silicone Rubber Coated Woven Fiberglass Tape

Non-Adhesive

High Temperature, Heat & Flame Resistant Heavy Duty Tape & Wrap



Heavy Duty Tape & Wrap, from ½” through 40” wide is made from our heaviest grade 98 oz/yd² material.

This tape is made from a heavy woven base fabric, which provides for very little elongation capability. This tape is stiffer than the AB-FT series tapes

This tape can also be layered and stitched with either face on each side. Multiply price by 2.5 times for 2 layer tape.

FlameShield™ High Temperature Silicone Rubber Coated Fiberglass Heavy Duty Tape & Wrap

Part Number	Width inch / mm / -dash	Price per foot	Price per Metre
T-SR-FGHD-M013-08	½ / 13 / -08	\$ 2.27	\$ 7.45
T-SR-FGHD-M019-12	¾ / 19 / -12	\$ 2.77	\$ 9.09
T-SR-FGHD-M025-16	1 / 25 / -16	\$ 3.37	\$ 11.05
T-SR-FGHD-M032-20	1 ¼ / 32 / -20	\$ 3.89	\$ 12.76
T-SR-FGHD-M038-24	1 ½ / 38 / -24	\$ 4.42	\$ 14.50
T-SR-FGHD-M044-28	1 ¾ / 44 / -28	\$ 4.81	\$ 15.78
T-SR-FGHD-M051-32	2 / 51 / -32	\$ 5.01	\$ 16.43
T-SR-FGHD-M057-36	2 ¼ / 57 / -36	\$ 5.58	\$ 18.30
T-SR-FGHD-M064-40	2 ½ / 64 / -40	\$ 6.13	\$ 20.11
T-SR-FGHD-M070-44	2 ¾ / 70 / -44	\$ 6.67	\$ 21.88
T-SR-FGHD-M076-48	3 / 76 / -48	\$ 6.91	\$ 22.66
T-SR-FGHD-M083-52	3 ¼ / 83 / -52	\$ 7.81	\$ 25.62
T-SR-FGHD-M089-56	3 ½ / 89 / -56	\$ 8.68	\$ 28.47
T-SR-FGHD-M095-60	3 ¾ / 95 / -60	\$ 9.44	\$ 30.96
T-SR-FGHD-M102-64	4 / 102 / -64	\$ 10.01	\$ 32.83
T-SR-FGHD-M108-68	4 ¼ / 108 / -68	\$ 10.61	\$ 34.80
T-SR-FGHD-M114-72	4 ½ / 114 / -72	\$ 11.37	\$ 37.30
T-SR-FGHD-M121-76	4 ¾ / 121 / -76	\$ 11.97	\$ 39.26
T-SR-FGHD-M127-80	5 / 127 / -80	\$ 12.84	\$ 42.12
T-SR-FGHD-M133-84	5 ¼ / 133 / -84	\$ 13.79	\$ 45.23
T-SR-FGHD-M140-88	5 ½ / 140 / -88	\$ 14.71	\$ 48.25
T-SR-FGHD-M146-92	5 ¾ / 146 / -92	\$ 15.65	\$ 51.33
T-SR-FGHD-M152-96	6 / 152 / -96	\$ 16.58	\$ 54.38
T-SR-FGHD-M159-100	6 ¼ / 159 / -100	\$ 17.47	\$ 57.30
T-SR-FGHD-M165-104	6 ½ / 165 / -104	\$ 18.39	\$ 60.32
T-SR-FGHD-M171-108	6 ¾ / 171 / -108	\$ 19.27	\$ 63.21
T-SR-FGHD-M178-112	7 / 178 / -112	\$ 20.18	\$ 66.19
T-SR-FGHD-M184-116	7 ¼ / 184 / -116	\$ 21.09	\$ 69.18
T-SR-FGHD-M191-120	7 ½ / 191 / -120	\$ 22.02	\$ 72.23
T-SR-FGHD-M197-124	7 ¾ / 197 / -124	\$ 22.98	\$ 75.37
T-SR-FGHD-M203-128	8 / 203 / -128	\$ 23.87	\$ 78.29
T-SR-FGHD-M210-132	8 ¼ / 210 / -132	\$ 24.84	\$ 81.48
T-SR-FGHD-M216-136	8 ½ / 216 / -136	\$ 25.78	\$ 84.56
T-SR-FGHD-M222-140	8 ¾ / 222 / -140	\$ 26.81	\$ 87.94
T-SR-FGHD-M229-144	9 / 229 / -144	\$ 27.85	\$ 91.35
T-SR-FGHD-M235-148	9 ¼ / 235 / -148	\$ 28.47	\$ 93.38
T-SR-FGHD-M241-152	9 ½ / 241 / -152	\$ 28.94	\$ 94.92
T-SR-FGHD-M248-156	9 ¾ / 248 / -156	\$ 29.53	\$ 96.86
T-SR-FGHD-M254-160	10 / 254 / -160	\$ 30.03	\$ 98.50

Add “-C4” for double layer stitched (approx .27”) thick

Tape is nominal 0.1350” / 3.4mm thick nominal single layer.

This product is available By-The-Foot. For sizes larger than 10” wide please call for a quote

500°F / 260°C continuous rating with weld splatter / molten metal splash protection.

To aid in mounting this tape onto surfaces, FlangeStik™ pressure sensitive adhesive spray can be used to place the tape in situ temporarily. Permanent fasteners or grab strips should be installed prior to heating of the area sprayed above 200°F. The adhesive will “smoke-off” at elevated temperatures.