

**Firesleeve End Wrap Tape / High Temperature Electrical Tape 500°F/260°C
Silicone Rubber Self Fusing / Self Binding / Self Amalgamating Compression Tape**



FlameShield™ end wrap & electrical amalgamating compression tape is a unique adhesive-free tape which self-fuses / self-bonds within 24 hours or less at room temperature or shorter time at elevated temperatures when wrapped over itself, providing an excellent water-tight and air-tight seal.

Tape is adhesive free; leaves no residue when removed. Typically used to protect the free ends of firesleeve from wicking liquids once installed on hoses or cables. Also used for electrical wire and cable splice protection and protection of wires at connector shell clamp band locations. Exceptional electrical insulation resistance in a single wrap.

Tested to:

- ASTM D 149; provides minimum 400 V/mil. for .010" to .030" thick tape, 300 V/mil for .040" thick tape and 250 V/mil for .060" thick tape.
- ASTM D 412; provides minimum 700 psi tensile strength and minimum 300% elongation.
- ASTM D 2240; Durometer (Shore A); 55. Other test data available.

Using triangular profile tapes results in a smooth surface contour when spiral wrapped. The most common tapes are 1" wide triangular profile with either a 0.020" or 0.040" center thickness. Meets Mil-I-46852C & A-A-59163 specifications. Triangular tapes have a center guideline to aid in properly spacing the tape when spiral wrapping. T-SR-SA25 tape meets MIL-I-22444 and provides uniform thickness even on sharp corners and edges.

Tape part numbers ending in "BK" are Black color; "OR" are Oxide-Red color. Other colors are available by custom run.

| FlameShield™ High Temperature Silicone Self Fusing Firesleeve End Wrap Tape | | | | |
|--|-----------------------------------|----------------------------------|--------------------------------|---------------------------------------|
| Meets MIL-I-46852 / A-A-59163 / ABS 5334 Specifications - Type I and Type II | | | | |
| Part Number | Tape Width Inches / mm | Thickness inches / mm | Color / Type / Profile | Single Roll Price Per Roll |
| T-SR-M013-08-RBK-20 | 1/2 / 12.7 | 0.020 / 0.508 | Black / I / Rectangular | \$ 29.37 |
| T-SR-M013-08-RXX-30 | 1/2 / 12.7 | 0.030 / 0.760 | Black or Red / I / Rectangular | \$ 37.16 |
| T-SR-M016-10-RBK-20 | 5/8 / 15.7 | 0.020 / 0.508 | Black / I / Rectangular | \$ 30.17 |
| T-SR-M019-12-ROR-10 | 3/4 / 19 | 0.010 / 0.254 | Oxide-Red / I / Rectangular | \$ 23.85 |
| T-SR-M019-12-RBK-20 | 3/4 / 19 | 0.020 / 0.508 | Black / I / Rectangular | \$ 31.96 |
| T-SR-M025-16-TXX-20 | 1 / 25.4 | 0.020 / 0.508 | Black or Red / II / Triangular | \$ 33.80 |
| T-SR-M025-16-RXX-20 | 1 / 25.4 | 0.020 / 0.508 | Black or Red / I / Rectangular | \$ 34.71 |
| T-SR-M025-16-TXX-40 | 1 / 25.4 | 0.040 / 1.000 | Black or Red / II / Triangular | \$ 37.91 |
| T-SR-M025-16-RXX-40 | 1 / 25.4 | 0.040 / 1.000 | Black or Red / I / Rectangular | \$ 39.64 |
| T-SR-M038-24-RXX-20 | 1 1/2 / 38.1 | 0.020 / 0.508 | Black or Red / I / Rectangular | \$ 48.77 |
| T-SR-M038-24-RXX-12 | 1 1/2 / 38.1 | 0.012 / 0.304 | Black or Red / I / Rectangular | \$ 38.47 |
| T-SR-M051-32-RXX-20 | 2 / 50.8 | 0.020 / 0.508 | Black or Red / I / Rectangular | \$ 57.13 |
| T-SR-M051-32-TXX-20 | 2 / 50.8 | 0.020 / 0.508 | Black or Red / II / Triangular | \$ 48.86 |
| Triangular Type II Tapes Only: .020" has a blue guideline / .040" has a green guideline | | | | |

| Supported Tape with Limited Elongation Meets MIL-I-22444 (also meets MIL-I-46852 / A-A-59163 / ABS 5334 Specifications) | | | | |
|--|----------|---------------|-------------------------|----------|
| T-SR-SA25-16-20-RBK* | 1 / 25.4 | 0.020 / 0.508 | Black / I / Rectangular | \$ 67.29 |
| T-SR-SA25-16-20-ROR* | 1 / 25.4 | 0.020 / 0.508 | Red / I / Rectangular | \$ 67.29 |

* NOTE: T-SR-SA25-16-20-RBK & T-SR-SA25-16-20-ROR tape has a built-in sinusoidal weave fiberglass reinforcement layer, limiting stretch of the tape to a maximum of 25%, ensuring that the tape thickness remains constant over irregular surfaces and edges.

A Certificate of Conformity is available at \$6.00 per roll or \$25.00 per line item / batch-lot. Test report is available at \$75.00 per line item. This tape is also available meeting several other OEM and National Stock Number / NATO Stock Number specifications (available under military cage code is L8347).

These tapes are guaranteed to meet specification for 1 year from date of manufacture providing tapes are stored dry at 21°C +/- 3°C or 70°F +/- 5°F. Standard tapes have an interleaved liner of polyethylene (Mylar®). Polyester liner available.