

Sleeve & Firesleeve Accessories:

End Seal Dip / End Wrap Tape / Clamps / Clamp Tools



SleeveSeal™

End Seal Dip – Liquid Silicone Rubber

The ends of firesleeve can be sealed against the absorption of liquids by dipping the end in this liquid silicone rubber end dip sealant. Available in any color: Oxide-Red and Black are the most common. Becomes tack free in 60 minutes and cures fully in 8 hours. 500°F / 260°C rating. Non-hazardous to ship and may be thinned with odourless mineral spirits (xylene).

- 4 oz Mini which can accommodate sleeve up to 1 3/4" ID. P/N: US-ESD-04-XX \$ 15.61
- 16 oz standard wide-mouth jar which can accommodate sleeve up to 3 1/4" ID. P/N: US-ESD-16-XX \$ 43.47
- 1 gallon jug. P/N: US-ESD-128-XX \$ 229.32
5 gallon pail. P/N: US-ESD-640-XX \$ 988.40. Larger bulk quantities are available.
- XX = "OR" for oxide-red or "BK" for black.

SleeveSeal™

End Seal Paste – Silicone Rubber RTV

This sealing paste can be used on firesleeve to prevent the absorption of liquids. Available in any color: Oxide-Red and Black are the most common. Cures in 24 hours at room temperature. 500°F / 260°C rating. Non-hazardous to ship.

Available in two sizes:

- 3 oz squeeze tube. P/N: US-ESP-03-XX \$ 15.61
- 10.3 oz cartridge. P/N: US-ESP-10-XX \$ 33.47
- XX = "OR" for oxide-red or "BLK" for black.



Desiccant box can be placed with uncured SleeveSeal Dip container in a sealed container or bag to considerably extend shelf life. Can be re-generated for unlimited re-use.

- P/N: AB-SGD-1 \$11.87

FlameShield™ End Wrap Tape – Silicone Rubber Self Fusing / Self Amalgamating



FlameShield™ end wrap tape is a unique adhesive-free tape which self-fuses / self-bonds when wrapped over itself, providing an excellent water-tight and air-tight seal. Leaves no residue when removed. Typically used to protect the free ends of firesleeve from wicking liquids once installed on hoses or cables. The triangular profile of 1" wide tapes results in a smooth surface contour when spiral wrapped.

Our most popular end wrap sealing tapes:

- 1" wide tape, 36 feet long, triangular profile. \$33.80
P/N: T-SRET-16-20-TOR for oxide-red
P/N: T-SRET-16-20-TBK for black
- 1" wide tape, 36 feet long, rectangular profile. \$34.71
P/N: T-SRET-16-20-ROR for oxide-red
P/N: T-SRET-16-20-RBK for black
- 1.5" wide tape, 36 feet long, rectangular profile. \$48.77
P/N: T-SRET-24-20-ROR for oxide-red
P/N: T-SRET-24-20-RBK for black

This tape is also available certified to AA-59163 and Mil-i-46852C. Certificate of Conformity is available at \$5.00. (Test result CofC is available at \$15.00). This tape is available meeting several NSN numbers including: 5970009494846, 5970009559976. Reinforced version meeting Mil-I-22444 available.

See page 2-4 for more of these tapes.